


ZU506T

High brightness professional laser projector



- **Bright WUXGA laser projector - 5000 ANSI lumens**
- **30,000 hours maintenance-free laser light source at full brightness**
- **4K, HDR Compatible**
- **HDBaseT**



Professional life like colours and a smaller lighter chassis than ever before. 4K and HDR compatible, the ZU506T is a low maintenance projector with extremely long-life laser technology at an impressive 5000lms.

Specifications

Display and image	
ProjDisplayTechnology	DLP™
ProjNativeResolution	WUXGA (1920x1200)
ProjBrightnessBrightLumens	5.000
ANSI brightness	5.000
ProjContrastRatio	300.000
NativeAspectRatio	16:10
SupportedAspectRatio	4:3, 16:9, 16:10
ProjKeystoneCorrectionHorizontal	+/-30°
ProjKeystoneCorrectionVertical	+/-30°
ProjAutoKeystoneVertical	Yes
ProjDisplayableColoursMillions	1073.4
ProjHorizontalScanRateKhz	15.375 ~ 91.146
ProjVerticalScanRateHz	50 ~ 85 Hz (120Hz for 3D)
ProjUniformityPercent	85
Screen size	0.53m ~ 8.42m (20.8" ~ 331.6") diagonal

Lamp info	
ProjLightSource	DuraCore Laser
ProjLaserHours	30.000

Optical	
ThrowRatio	1.4:1 ~ 2.24:1
ProjectionDistanceMetres	1m - 10m
FixedLensZoom	1.6
FixedLensZoomType	Manual
FixedLensFocalLength	20.91 ~ 32.62
FixedLensShift	Vertical -99 ~ 107%
ProjNativeOffset	99%
Lens shift	Yes - {{downloads_link}}

Connectivity	
Connections	<p>Inputs 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support, 2 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Mic 3.5mm, 1 x Audio 3.5mm, 1 x HDBaseT, 1 x S-Video</p> <p>Outputs 1 x VGA, 1 x USB-A power 1.5A, 1 x Audio 3.5mm, 1 x RJ45</p> <p>Control 1 x RS232, 1 x 12V trigger</p>

General	
NoiseLevelTypicalDb	28
NoiseLevelMaxDb	33
PcCompatibility	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
Proj2DCompatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
Proj3DCompatibility	Side-by-Side: 1080i 50/60, 720p 50/60 Frame-pack: 1080p 24, 720p 50/60 Over-Under: 1080p 24, 720i 50/60
Proj3DType	Full 3D
ProductSecurity	Security bar, Kensington Lock, Password protected interface
IP rating	IP5X
OSDLangs	1 languages:
TwentyFourSevenOperation	Yes
ThreeSixtyDegreeOperation	Yes
OperatingConditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
RemoteControl	Backlit ProAV remote
SpeakerCount	2
SpeakerWatts	10
In the box	AC power cord Remote control
Optional wireless models	HDCast Pro, QuickCast Bundle, QuickCast starter kit

Networking	
LanControl	Yes

Power	
PowerSupply	100V ~ 240V, 50-60Hz
PowerConsumptionWattsStandby	<0.5
PowerConsumptionWattsMin	218
PowerConsumptionWattsMax	361

Weight and dimensions	
ProductDimensions	374 x 302 x 107
Gross weight	7.8 kg
Net weight	5.5 kg

