

ZU920TST

Ultra bright fixed lens laser projector



- **9800 lumen DuraCore laser projector - Ultra bright for immersive installations**
- **Full motorised lens shift - Ideal for a simple set up**
- **Large zoom range - Motorised zoom expands placement opportunities**
- **Long life - Delivers 30,000 hours of virtually maintenance-free operation**



At 9800 lumens with 4K and HDR compatibility, the ZU920TST features a dust-resistant IP5X certified optical engine for 24/7 operation capabilities, offering true maintenance-free projection for up to 30,000 hours of powerful performance in Eco mode. Other features include a motorised zoom, full motorised lens shift and built-in dual 10W speakers.

High brightness, colour precision and quiet operation, along with a short throw lens make this projector the ideal solution for a variety of end-user scenarios and professional environments.

Specifications

Display and image	
ProjDisplayTechnology	DLP
ProjNativeResolution	WUXGA (1920x1200)
ProjBrightnessBrightLumens	9.800
ProjContrastRatio	3.000.000
NativeAspectRatio	16:10
SupportedAspectRatio	4:3,16:9,16:10
ProjKeystoneCorrectionHorizontal	30°
ProjKeystoneCorrectionVertical	30°
ProjUniformityPercent	95
Screen size	1.27m ~ 7.62m (50" ~ 300") diagonal
Lamp info	
ProjLightSource	DuraCore Laser
ProjLaserHours	30.000
Optical	
ThrowRatio	0.65:1 ~ 0.75:1
ProjectionDistanceMetres	0.7m - 16.6m
FixedLensZoom	1.15
FixedLensZoomType	Motorised
FixedLensFocalLength	9.69-11.19
FixedLensShift	Vertical: +/-110%, Horizontal: +/-50%
ProjNativeOffset	50%
Lens shift	Yes - {{downloads_link}}
Connectivity	
Connections	Inputs 1 x HDBaseT, 1 x HDMI 2.0, 1 x HDMI 2.0, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232
LANWirelessNetworking	No
General	
NoiseLevelTypicalDb	36
NoiseLevelMaxDb	38
ProductSecurity	Security bar, Kensington Lock
IP rating	IP5X
TwentyFourSevenOperation	Yes
ThreeSixtyDegreeOperation	Yes
RemoteControl	Backlit ProAV remote
SpeakerCount	2
SpeakerWatts	10
Networking	
LanControl	Yes
LANWirelessNetworking	No
LanDHCP	Yes
Power	
PowerSupply	AC 90 – 264V 50/60 Hz
PowerConsumptionWattsMin	265
PowerConsumptionWattsMax	520
Weight and dimensions	
ProductDimensions	480 x 376 x 144
Gross weight	17.5 kg
Net weight	14 kg

