

GT1080HDR

Short throw, bright and compact









- Bright 1080p projector 3,800 Lumens
- Shorter installation distance with short throw lens design
- Easy connectivity HDMI, VGA, USB power
- 4K Signal / HDR Compatible

Transform the delivery of your movie and gaming time with the first ever 3,800 lumens, 1080p, short throw design GT1080HDR projector. This model is designed to be used at any time of day and for every home entertainment scenario. It offers top quality projected colors, long lamp life with a low overall cost of ownership.

This full HD product boasts simplicity in design, with easy navigation and reliability. Convenient, with multiple inputs including HDMI and MHL, this projector is ideal for connecting HDMI dongles such as the Google Chromecast and the Optoma HDCast Pro enabling you to connect your laptop, PC or Blu-ray player. This compact model can either be installed or conveniently taken on the move.

Specifications

Display/image DIPTM Display technology

Resolution 1080p Full HD (1920x1080)

Brightness 3,800 lumens Contrast ratio 50,000:1 16:9 Native aspect ratio 4:3,16:9 Aspect ratio - compatible Keystone correction - vertical +/-40°

Horizontal scan rate 15.38 ~ 91.15Khz Vertical scan rate 50 ~ 85(120 for 3D)Hz

70% Uniformity

Screen size 0.92m ~ 7.82m (36.2" ~ 307.8") diagonal

Lamp info

Light source type Lamp

4000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+) Lamp life hours (up to)

Optical Throw ratio 0.49:1 Projection distance 0.4m - 3.5m 7.42mm Focal length Native offset 116%

Connectivity

3D compatibility

Connections Inputs 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support + MHL, 1 x

VGA, 1 x Audio 3.5mm

Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A

Control 1 x RS232

General Noise level (typical) 26dB Noise level (max) 28dB

PC compatibility UHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA,

2D compatibility NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz

SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60

Full 3D 3D

Security Security bar, Kensington Lock, Password protected interface

OSD / display languages 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese

Operating conditions 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%

Speaker count Watts per speaker 10W In the box AC power cord Remote control

Basic user manual Power 100 ~ 240V, 50 ~ 60Hz

Power supply Power consumption (standby) 0.5W

205W Power consumption (min) Power consumption (max) 325W

Weight and dimensions Dimensions (W x D x H)

316 x 243.5 x 115 Gross weight 4.7 kg 3.5 kg Net weight





