

ZU1100

Spectacular image quality, low maintenance and ultimate reliability.



- **High brightness WUXGA DLP laser projector - 11,500 lumens**
- **DuraCore laser technology - Up to 30,000 hours laser light source**
- **Dust resistant - Independently tested, IP6X certified for total reliability**
- **Installation flexibility - 7 interchangeable lens options including an ultra short throw lens**



The ZU1100 offers enhanced features such as built-in edge-blending and warping. Part of the DuraCore laser lineup, it combines a longer-lifetime light source and an independent IP-rated dust certification for ultimate peace of mind. Delivering up to an astonishing 30,000 hours laser light source, this projector achieves superior colour rendition producing visually striking lifelike images with exceptional detail.

Specifications

Display and image	
ProjDisplayTechnology	DLP
ProjNativeResolution	WUXGA (1920x1200)
ProjBrightnessBrightLumens	11.500
ANSI brightness	10.000
ProjContrastRatio	2.000.000
NativeAspectRatio	16:10
SupportedAspectRatios	16:9,16:10
Screen size	Dependent on lens
Lamp info	
ProjLightSource	DuraCore Laser
ProjLaserHours	30.000
Optical	
ThrowRatio	Dependent on lens
ProjectionDistanceMetres	Dependent on lens
Lens options	BX-CTA16 - 0.36 ~ 0.36 BX-CTA17 - 0.65~0.75 BX-CTA15 - 0.75 ~ 0.95 BX-CTA01 - 0.95 ~ 1.22 BX-CTA06 - 1.22 ~ 1.53 BX-CTA03 - 1.52 ~ 2.92 BX-CTA13 - 2.90 ~ 5.50
Connectivity	
Connections	Inputs 2 x HDMI 2.0, 1 x DVI-D, 1 x 3G-SDI, 1 x 3D sync, 1 x HDBaseT Outputs 1 x HDMI, 1 x 3D sync, 1 x USB-A power 2A Control 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x Wired remote
LANWirelessNetworking	No
General	
NoiseLevelTypicalDb	36
NoiseLevelMaxDb	38
PcCompatibility	HD, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh Compatible
Proj2DCompatibility	PAL (625/576i/p), SECAM, NTSC (525/480i/p), HDTV (720p, 1080i/1080p)
Proj3DCompatibility	Side-by-Side : 1080i 50/60, 720p 50/60 ; Frame-pack : 1080p 24 , 720p 50/60 ; Over-Under : 1080p 24, 720p 50/60
Proj3DType	Full 3D
ProductSecurity	Security bar, Kensington Lock
IP rating	IP6X
OSDLangs	1 languages:
TwentyFourSevenOperation	Yes
ThreeSixtyDegreeOperation	Yes
OperatingConditions	5°C~40°C/41°F~104°F, max altitude M/0ft, max humidity 10-85%
RemoteControl	Backlit ProAV remote
Networking	
LanControl	Yes
LanDisplay	Yes
LANWirelessNetworking	No
LanDHCP	Yes
Power	
PowerSupply	100 - 240V, 50 - 60Hz
PowerConsumptionWattsStandby	0.5
PowerConsumptionWattsMin	380
PowerConsumptionWattsMax	720
Weight and dimensions	
ProductDimensions	484 x 529 x 195
Gross weight	27 kg
Net weight	21 kg

