


ZU606TST-B

High brightness professional laser projector



- **Bright WUXGA short throw laser projector - 6,300 lumens**
- **30,000 hours maintenance-free laser light source at full brightness**
- **4K and HDR compatible**
- **HDBaseT Connectivity**

Introducing the ZU606TST-B, the smallest projector in its class. At 6,300 lumens with 4K and HDR compatibility, the ZU606TST-B is a low maintenance projector with extremely long-life laser technology. With a 0.79:1 throw ratio, vertical lens shift and built-in 10W speakers.

Suitable for a wide variety of applications, the ZU606TST-B is perfect for anywhere that requires a clean bright image including large venues, classrooms/lecture theatres, museums and houses of worship.

The added control flexibility of HDBaseT and LAN make this projector an affordable fit and forget solution.

Specifications

Display and image	
ProjDisplayTechnology	DLP™
ProjNativeResolution	WUXGA (1920x1200)
ProjBrightnessBrightLumens	6.300
ProjContrastRatio	300.000
NativeAspectRatio	16:10
SupportedAspectRatio	4:3,16:9,16:10
ProjKeystoneCorrectionHorizontal	+/-30°
ProjKeystoneCorrectionVertical	+/-30°
ProjAutoKeystoneVertical	Yes
ProjDisplayableColoursMillions	1073.4
ProjHorizontalScanRateKhz	15.375~91.146
ProjVerticalScanRateHz	24~ 85 Hz (120Hz for 3D)
ProjUniformityPercent	85
Screen size	0.75m ~ 7.76m (29.38" ~ 305.6") diagonal
Lamp info	
ProjLightSource	DuraCore Laser
ProjLaserHours	30.000
Optical	
ThrowRatio	0.79:1
ProjectionDistanceMetres	0.5m - 5.2m
FixedLensZoomType	Fixed
FixedLensFocalLength	11.66
FixedLensShift	Vertical -100 ~ 120%
ProjNativeOffset	100%
Lens shift	Yes - {{downloads_link}}
Connectivity	
Connections	<p>Inputs 1 x HDMI 1.4a 3D support, 1 x HDMI 1.4a 3D support + MHL, 2 x VGA, 1 x Composite video, 1 x Mic 3.5mm, 1 x Audio 3.5mm, 1 x HDBaseT, 1 x S-Video</p> <p>Outputs 1 x VGA, 1 x USB-A power 1.5A, 1 x Audio 3.5mm</p> <p>Control 1 x RS232, 1 x 12V trigger, 1 x RJ45</p>
General	
NoiseLevelTypicalDb	33
NoiseLevelMaxDb	38
PcCompatibility	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
Proj2DCompatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(24/50/60Hz)
Proj3DCompatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
Proj3DType	Full 3D
ProductSecurity	Security bar, Kensington Lock, Password protected interface
IP rating	IP6X
OSDLangs	1 languages:
TwentyFourSevenOperation	Yes
OperatingConditions	Sea Level to 10,000 feet (@23°C); manual switch to high altitude mode @5000 feet & above
RemoteControl	Backlit ProAV remote
HeatDissipationBtuHour	1.328
SpeakerCount	2
SpeakerWatts	10
In the box	AC power cord Remote control
Networking	
LanControl	Yes
LanDHCP	Yes
Power	
PowerSupply	100V ~ 240V , 50-60Hz
PowerConsumptionWattsStandby	0.5
PowerConsumptionWattsMin	220
PowerConsumptionWattsMax	476
Weight and dimensions	
ProductDimensions	374 x 302 x 107
Gross weight	7.8 kg
Net weight	5.5 kg

