


# ZU606T

High brightness professional laser projector



- **Bright WUXGA laser projector - 6,000 lumens**
- **30,000 hours maintenance-free laser light source at full brightness**
- **4K and HDR compatible**
- **HDBaseT Connectivity**

Introducing the ZU606T, the smallest projector in its class. At 6,000 lumens with 4K and HDR compatibility, the ZU606T is a low maintenance projector with extremely long-life laser technology also including vertical lens shift and built-in 10W speakers.

Suitable for a wide variety of applications, this unit is perfect for anywhere that requires a clean bright image including large venues, classrooms/lecture theatre's, museums and houses of worship.

The added control flexibility of HDBaseT and LAN make this projector an affordable fit and forget solution.

## Specifications

<b>Display/image</b>	
Display technology	DLP™
Resolution	WUXGA (1920x1200)
Brightness	6,000 lumens
Contrast ratio	3,000,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9,16:10
Keystone correction - horizontal	+/-30°
Keystone correction - vertical	+/-30°
Has vertical auto keystone correction	Yes
Displayable colours (millions)	1073.4
Horizontal scan rate	15.375-91.146 Khz
Vertical scan rate	24- 85 Hz (120Hz for 3D)Hz
Uniformity	85%
Screen size	0.8m ~ 7.67m (31.5" ~ 301.8") diagonal
<b>Lamp info</b>	
Light source type	DuraCore Laser
LASER life	30,000 hours
<b>Optical</b>	
Throw ratio	1.2:1 ~ 1.92:1
Projection distance	1.3m - 7.8m
Zoom	1.6
Zoom type	Manual
Focal length	11.66
Lens shift	Vertical -100 ~ 120%
Native offset	100%
Lens shift	Yes - <a href="#">{{downloads_link}}</a>
<b>Connectivity</b>	
Connections	<p><b>Inputs</b> 1 x HDMI 1.4a 3D support, 1 x HDMI 2.0, 2 x VGA, 1 x Composite video, 1 x Mic 3.5mm, 1 x Audio 3.5mm, 1 x HDBaseT, 1 x S-Video</p> <p><b>Outputs</b> 1 x VGA, 1 x USB-A power 1.5A, 1 x Audio 3.5mm</p> <p><b>Control</b> 1 x RS232, 1 x 12V trigger, 1 x RJ45</p>
LAN - wireless networking	No
<b>General</b>	
Noise level (typical)	32dB
Noise level (max)	34dB
PC compatibility	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(24/50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
IP rating	IP6X
OSD / display languages	1 languages:
24/7 operation	Yes
Operating conditions	Sea Level to 10,000 feet (@23°C); manual switch to high altitude mode @5000 feet & above
Remote control	Backlit ProAV remote
Heat dissipation	1,521BTU/hour
Speaker count	2
Watts per speaker	10W
In the box	AC power cord Remote control
<b>Networking</b>	
LAN - control	Yes
LAN - wireless networking	No
LAN	Yes
<b>Power</b>	
Power supply	100V ~ 240V , 50-60Hz
Power consumption (standby)	0.5W
Power consumption (min)	216W
Power consumption (max)	467W
<b>Weight and dimensions</b>	
Dimensions (W x D x H)	374 x 302 x 107
Gross weight	7.5 kg
Net weight	5.5 kg

