

## **ZU820T**

Ultra-Bright fixed lens laser projector









- 8,800 Lumens Duracore laser projector Ultra bright for immersive installations
- Full motorised lens shift Ideal for a simple set up
- Large zoom range Motorised zoom expands placement opportunities
- Long life Delivers 30,000 hours of virtually maintenance-free operation



At 8,800 lumens with 4K and HDR compatibility, the ZU820T features a dust-resistant IP5X certified optical engine for 24/7 operation capabilities, offering true maintenance-free projection for up to 30,000 hours of powerful performance in Eco mode. Other features include a motorised zoom, full motorised lens shift and built-in dual 10W speakers.

High brightness, colour precision and quiet operation, alongside a 1.6x zoom make this projector the ideal solution for a variety of end-user scenarios and professional environments, such as simulation, edge-blending and projection mapping, and immersive installations.

## **Specifications**

Display/image Display technology DIP

Resolution WUXGA (1920x1200) Brightness 8,800 lumens 3,000,000:1 Contrast ratio Contrast ratio - full on/off 1,100:1 Native aspect ratio 16:10 Aspect ratio - compatible 4:3,16:9,16:10

Keystone correction -30° horizontal

Keystone correction - vertical 30° Uniformity 95%

1.27m ~ 7.62m (50" ~ 300") diagonal Screen size

Lamp info Light source type DuraCore Laser LASER life 30,000 hours Optical 1.25:1 ~ 2:1 Throw ratio Projection distance 0.8m - 21.5m Zoom 1.6 Zoom type Motorised Focal length 18.72~29.59 Vertical: +/-110%, Horizontal: +/-50% Lens shift

Lens shift Yes - {{downloads\_link}}

Connectivity Connections Inputs 1 x HDBaseT, 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm

Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm

Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x

No LAN - wireless networking

General Noise level (typical) 34dB Noise level (max) 36dB 3D Full 3D

Security Security bar, Kensington Lock

IP rating IP5X 24/7 operation Yes 360° operation Yes

Remote control Backlit ProAV remote Speaker count 2

10W Watts per speaker Networking

LAN - control Yes LAN - wireless networking No LAN Yes

Power Power supply AC 90 - 264V 50/60 Hz with PFC input

Power consumption (standby) 0.5W 265W Power consumption (min) Power consumption (max) 520W

Weight and dimensions

Dimensions (W x D x H) 486 x 432.5 x 176 Gross weight 17.5 kg Net weight 14 kg





