

## ZU920T Ultra bright fixed lens laser projector



- 9800 lumen DuraCore laser projector Ultra bright for immersive installations
- Full motorised lens shift Ideal for a simple set-up
- Large zoom range Motorised zoom expands placement opportunities
- Long life Delivers 30,000 hours of virtually maintenance-free operation



At 9,800 lumens with 4K and HDR compatibility, the ZU920T features a dust-resistant IP5X certified optical engine for 24/7 operation capabilities, offering true maintenance-free projection for up to 30,000 hours of powerful performance in Eco mode. Other features include a motorised zoom, full motorised lens shift and built-in dual 10W speakers.

High brightness, colour precision and quiet operation, along with a short throw lens make this projector the ideal solution for a variety of end-user scenarios and professional environments, such as short throw digital signage, edge-blending and projection mapping, simulation, and immersive installations.

## **Specifications**

Display and image	
ProjDisplayTechnology	DLP
ProjNativeResolution	WUXGA (1920x1200)
ProjBrightnessBrightLumens	9.800
ProjContrastRatio	3.000.000
ProjContrastRatioFullOnOff	1.100
NativeAspectRatio	16:10
SupportedAspectRatios	4:3,16:9,16:10
ProjKeystoneCorrectionHorizontal	30°
ProjKeystoneCorrectionVertical	30°
ProjUniformityPercent	95
Screen size	1.27m ~ 7.62m (50" ~ 300") diagonal
Lamp info	
ProjLightSource	DuraCore Laser
ProjLaserHours	30.000
Optical	
ThrowRatio	1.25:1 ~ 2:1
ProjectionDistanceMetres	1.33m - 13.06m
FixedLensZoom	1.6
FixedLensZoomType	Motorised
FixedLensFocalLength	18.72~29.59
FixedLensShift	Vertical: +/-110%, Horizontal: +/-50%
ProjNativeOffset	50%
Lens shift	Yes - {{downloads_link}}
Connectivity	
Connections	Inputs 1 x HDBaseT, 2 x HDMI 2.0, 1 x VGA, 1 x 3D sync, 1
	x Audio 3.5mm
	Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A,
	1 x Audio 3.5mm
	<b>Control</b> 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x
	RS232
LANWirelessNetworking	No
General	No
General NoiseLevelTypicalDb	No 36
General NoiseLevelTypicalDb NoiseLevelMaxDb	No 36 38
General NoiseLevelTypicalDb NoiseLevelMaxDb ProductSecurity	No 36 38 Security bar, Kensington Lock
General NoiseLevelTypicalDb NoiseLevelMaxDb ProductSecurity IP rating	No 36 38 Security bar, Kensington Lock IP5X
General NoiseLevelTypicalDb NoiseLevelMaxDb ProductSecurity IP rating TwentyFourSevenOperation	No 36 38 Security bar, Kensington Lock IP5X Yes
General NoiseLevelTypicalDb NoiseLevelMaxDb ProductSecurity IP rating TwentyFourSevenOperation ThreeSixtyDegreeOperation	No 36 38 Security bar, Kensington Lock IP5X Yes Yes
General NoiseLevelTypicalDb NoiseLevelMaxDb ProductSecurity IP rating TwentyFourSevenOperation ThreeSixtyDegreeOperation RemoteControl	No 36 38 Security bar, Kensington Lock IP5X Yes Yes Backlit ProAV remote
General NoiseLevelTypicalDb NoiseLevelMaxDb ProductSecurity IP rating TwentyFourSevenOperation ThreeSixtyDegreeOperation RemoteControl SpeakerCount	No 36 38 Security bar, Kensington Lock IP5X Yes Yes Backlit ProAV remote 2
General NoiseLevelTypicalDb NoiseLevelMaxDb ProductSecurity IP rating TwentyFourSevenOperation ThreeSixtyDegreeOperation RemoteControl SpeakerCount SpeakerWatts	No 36 38 Security bar, Kensington Lock IP5X Yes Yes Backlit ProAV remote
General NoiseLevelTypicalDb NoiseLevelMaxDb ProductSecurity IP rating TwentyFourSevenOperation ThreeSixtyDegreeOperation RemoteControl SpeakerCount SpeakerCount SpeakerWatts Networking	No 36 38 Security bar, Kensington Lock IP5X Yes Yes Backlit ProAV remote 2 10
General NoiseLevelTypicalDb NoiseLevelMaxDb ProductSecurity IP rating TwentyFourSevenOperation ThreeSixtyDegreeOperation RemoteControl SpeakerCount SpeakerCount SpeakerWatts Networking LanControl	No 36 38 Security bar, Kensington Lock IP5X Yes Yes Backlit ProAV remote 2 10 Yes
General NoiseLevelTypicalDb NoiseLevelMaxDb ProductSecurity IP rating TwentyFourSevenOperation ThreeSixtyDegreeOperation RemoteControl SpeakerCount SpeakerCount SpeakerWatts Networking LanControl LANWirelessNetworking	No 36 38 Security bar, Kensington Lock IP5X Yes Yes Backlit ProAV remote 2 10 Yes No
General NoiseLevelTypicalDb NoiseLevelMaxDb ProductSecurity IP rating TwentyFourSevenOperation ThreeSixtyDegreeOperation RemoteControl SpeakerCount SpeakerCount SpeakerWatts Networking LanControl LANWirelessNetworking LanDHCP	No 36 38 Security bar, Kensington Lock IP5X Yes Yes Backlit ProAV remote 2 10 Yes
General NoiseLevelTypicalDb NoiseLevelMaxDb ProductSecurity IP rating TwentyFourSevenOperation ThreeSixtyDegreeOperation RemoteControl SpeakerCount SpeakerCount SpeakerWatts Networking LanControl LANWirelessNetworking LanDHCP Power	No 36 38 Security bar, Kensington Lock IP5X Yes Yes Backlit ProAV remote 2 10 Yes No Yes
General NoiseLevelTypicalDb NoiseLevelMaxDb ProductSecurity IP rating TwentyFourSevenOperation ThreeSixtyDegreeOperation RemoteControl SpeakerCount SpeakerWatts Networking LanControl LANWirelessNetworking LanDHCP Power PowerSupply	No 36 38 Security bar, Kensington Lock IP5X Yes Backlit ProAV remote 2 10 Yes No Yes AC 90 – 264V 50/60 Hz
General NoiseLevelTypicalDb NoiseLevelMaxDb ProductSecurity IP rating TwentyFourSevenOperation ThreeSixtyDegreeOperation RemoteControl SpeakerCount SpeakerWatts Networking LanControl LANWirelessNetworking LanDHCP Power PowerSupply	No 36 38 Security bar, Kensington Lock IP5X Yes Yes Backlit ProAV remote 2 10 Yes No Yes
General NoiseLevelTypicalDb NoiseLevelMaxDb ProductSecurity IP rating TwentyFourSevenOperation ThreeSixtyDegreeOperation RemoteControl SpeakerCount SpeakerCount SpeakerWatts Networking LanControl LANWirelessNetworking LanDHCP Power Power PowerSupply PowerConsumptionWattsStandby PowerConsumptionWattsMin	No 36 38 Security bar, Kensington Lock IP5X Yes Backlit ProAV remote 2 10 Yes No Yes AC 90 – 264V 50/60 Hz 0.5 265
General NoiseLevelTypicalDb NoiseLevelMaxDb ProductSecurity IP rating TwentyFourSevenOperation ThreeSixtyDegreeOperation RemoteControl SpeakerCount SpeakerCount SpeakerWatts Networking LanControl LANWirelessNetworking LanDHCP Power PowerSupply PowerConsumptionWattsStandby	No 36 38 Security bar, Kensington Lock IP5X Yes Backlit ProAV remote 2 10 Yes No Yes AC 90 – 264V 50/60 Hz 0.5
General NoiseLevelTypicalDb NoiseLevelMaxDb ProductSecurity IP rating TwentyFourSevenOperation ThreeSixtyDegreeOperation RemoteControl SpeakerCount SpeakerCount SpeakerWatts Networking LanControl LANWirelessNetworking LanDHCP Power Power PowerSupply PowerConsumptionWattsStandby PowerConsumptionWattsMin	No 36 38 Security bar, Kensington Lock IP5X Yes Backlit ProAV remote 2 10 Yes No Yes AC 90 – 264V 50/60 Hz 0.5 265
General NoiseLevelTypicalDb NoiseLevelMaxDb ProductSecurity IP rating TwentyFourSevenOperation ThreeSixtyDegreeOperation RemoteControl SpeakerCount SpeakerCount SpeakerWatts Networking LanControl LANWirelessNetworking LanDHCP Power Power PowerSupply PowerConsumptionWattsStandby PowerConsumptionWattsMin PowerConsumptionWattsMin	No 36 38 Security bar, Kensington Lock IP5X Yes Backlit ProAV remote 2 10 Yes No Yes AC 90 – 264V 50/60 Hz 0.5 265
General NoiseLevelTypicalDb NoiseLevelMaxDb ProductSecurity IP rating TwentyFourSevenOperation ThreeSixtyDegreeOperation RemoteControl SpeakerCount SpeakerCount SpeakerWatts Networking LanControl LANWirelessNetworking LanDHCP Power Power PowerConsumptionWattsStandby PowerConsumptionWattsMin PowerConsumptionWattsMax Weight and dimensions	No           36           38           Security bar, Kensington Lock           IP5X           Yes           Yes           Backlit ProAV remote           2           10           Yes           No           Yes           AC 90 – 264V 50/60 Hz           0.5           265           520







Copyright © 2023, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 13092023105523