

# ZU1300

Spectacular image quality, low maintenance and ultimate reliability



- **High brightness WUXGA DLP laser projector - 14,400 lumens**
- **DuraCore laser technology - Up to 30,000 hours laser light source**
- **Dust resistant - Independently tested, IP6X certified for total reliability**
- **Installation flexibility - 7 interchangeable lens options including an ultra short throw lens**



The ZU1300 offers enhanced features such as built-in edge-blending and warping. Part of the DuraCore laser lineup, it combines a longer-lifetime light source and an independent IP-rated dust certification for ultimate peace of mind.

## Specifications

<b>Display and image</b>	
ProjDisplayTechnology	DLP
ProjNativeResolution	WUXGA (1920x1200)
ProjBrightnessBrightLumens	14,400
ANSI brightness	12,000
ProjContrastRatio	2,000,000
NativeAspectRatio	16:10
SupportedAspectRatio	16:9,16:10
Screen size	Dependent on lens
<b>Lamp info</b>	
ProjLightSource	DuraCore Laser
ProjLaserHours	30,000
<b>Optical</b>	
ThrowRatio	Dependent on lens
ProjectionDistanceMetres	Dependent on lens
Lens options	BX-CTA16 - 0.36 ~ 0.36 BX-CTA17 - 0.65~0.75 BX-CTA15 - 0.75 ~ 0.95 BX-CTA01 - 0.95 ~ 1.22 BX-CTA06 - 1.22 ~ 1.53 BX-CTA03 - 1.52 ~ 2.92 BX-CTA13 - 2.90 ~ 5.50
<b>Connectivity</b>	
Connections	<b>Inputs</b> 2 x HDMI 2.0, 1 x DVI-D, 1 x 3G-SDI, 1 x 3D sync, 1 x HDBaseT <b>Outputs</b> 1 x HDMI, 1 x 3D sync, 1 x USB-A power 2A <b>Control</b> 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x Wired remote
LANWirelessNetworking	No
<b>General</b>	
NoiseLevelTypicalDb	36
NoiseLevelMaxDb	38
PcCompatibility	HD, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh Compatible
Proj2DCompatibility	PAL (625/576i/p), SECAM, NTSC (525/480i/p), HDTV (720p, 1080i/1080p)
Proj3DCompatibility	Side-by-Side : 1080i 50/60, 720p 50/60 ; Frame-pack : 1080p 24 , 720p 50/60 ; Over-Under : 1080p 24, 720p 50/60
Proj3DType	Full 3D
ProductSecurity	Security bar, Kensington Lock
IP rating	IP6X
OSDLangs	1 languages:
TwentyFourSevenOperation	Yes
ThreeSixtyDegreeOperation	Yes
OperatingConditions	5°C~40°C/41°F~104°F, max altitude M/0ft, max humidity 10-85%
RemoteControl	Backlit ProAV remote
<b>Networking</b>	
LanControl	Yes
LanDisplay	Yes
LANWirelessNetworking	No
LanDHCP	Yes
<b>Power</b>	
PowerSupply	100 - 240V, 50 - 60Hz
PowerConsumptionWattsStandby	0.5W
PowerConsumptionWattsMin	465
PowerConsumptionWattsMax	955
<b>Weight and dimensions</b>	
ProductDimensions	484 x 529 x 195
Gross weight	27 kg
Net weight	21 kg

