Creative Touch 5-series IFP



| Size | 65" | 75" | 86" | | |
|---------------------------------|---|--------------------------|----------------------|--|--|
| Model | 5653RK | 5753RK | 5863RK | | |
| Display | | | | | |
| Back Light | | D-LED | | | |
| Resolution | 4K UHD (3,840 x 2,160) | | | | |
| Brightness | 400 cd/ m2 | 420 cd/ m2 | 450 cd/ m2 | | |
| Contrast Ratio | 4,000:1 | 4,000:1 | 4,000:1 | | |
| Viewing Angle | (6000:1 in DC Mode) (6000:1 in DC Mode (4500:1 in DC Mode 178° | | | | |
| Response Time | 1/8 6.5 ms | | | | |
| Life | 50,000 hours | | | | |
| Display Colors | 1.07 B (10 bit) | | | | |
| Speakers | 2 x 18W stereo speakers + 2 x 8W subwoofer | | | | |
| Surface Hardness | 3.2mm Toughened Glass with 7H Mohs Standard Anti-glare + Anti Finger print | | | | |
| Glass | Anti | -glare + Anti Finger | orint | | |
| Power | 1 | 100 0101 -010011 | | | |
| Power Supply | 100-240V, 50/60Hz ≤ 0.5W | | | | |
| Standby Power Power Cosumption | 415W | ≤ 0.5VV 530W | 570W | | |
| | 41014 | 33014 | 31044 | | |
| Dimensions | | | | | |
| Display Dimension (LxHxD) | 1488×908×86mm | 1709×1031×86mm | 1957×1171×86mm | | |
| Package L*H*D VESA Mount | 1628×1005×208mm √ | 1863×1148×225mm √ | 2110×1291x225mm √ | | |
| Net Weight | ν 39 kg | 52 kg | ν 64 kg | | |
| Gross Weight | 49 kg | 61 kg | 81 kg | | |
| Connectivity | | | | | |
| HDMI 2.0 In | 4 (2.0*3, Front*1 & Rear*1) | | | | |
| HDMI 2.0 Out | 4 (2.0°3, Front°1 & Rear°1) 1 (v2.0, 4K@60Hz) | | | | |
| VGA In | 1 (VZ.U, 4N(WUUTIZ) - | | | | |
| Audio In | 1 | | | | |
| Audio Out | 1 | | | | |
| SPDIF Out | | 1 | | | |
| Mic In DP In | - 4 (v4 2) | | | | |
| USB 2.0 | 1 (v1.2) 1 (FW upgrade) | | | | |
| USB 3.0 | 4 (Front*2, Side*2) | | | | |
| USB Touch Output | 2 | | | | |
| RS232 | 1 | | | | |
| LAN (RJ45) USB Type C In | 2 (Support 10/100/1000 Mbps) Front*1 & Rear*1 (both support 3.1 gen 1, 5 Gbit/s data transmission, DisplayPort 1.2 Alt Mode, 100M LAN network sharing) & Front port supports 100W power delivery (Limited to 65W with OPS) & Rear port support 15W power delivery. | | | | |
| USB Type C Out | Rear*1, DisplayPort 1.2, video out (4K@60Hz) & touch signal out. | | | | |
| OPS Slot | | Yes | | | |
| Touch System | | | | | |
| Touch Type | | Ultra-fine Infrared (IR) | | | |
| System Compatibility | Windows 10 / Windows 11 / Linux | | | | |
| Response Time | Mac OS / Android / Chrome OS ≤ 2.5 ms | | | | |
| Touch Point | ≦ ∠.5 ms Up to 50 points touch (32 points touch in Android, 50 points touch in Windows, 10 points writing) | | | | |
| Accuracy | 50 points touch in windows, 10 points writing) <1mm (over 90% Area) | | | | |
| Air Gap | Gen 2 Zero Bonding (0 ~ 0.6mm) | | | | |
| Writing Tools | Fingers, Passive Infrared Pen | | | | |
| Palm Rejection | Yes, supp | ort to coexist with Pa | alm Eraser | | |
| Embedded Syster | n | | | | |
| System Version | Android 13.0 with Google EDLA Certified | | | | |
| CPU | RK3588 (Quad Core A76 + Quad Core A55) | | | | |
| GPU RAM | ARM Quad-core Mali-G610 MC4 8 GB | | | | |
| ROM | 64 GB | | | | |
| WiFi / Bluetooth | D | ed On Optional Acces | 200m/ | | |

| Specifications (Continued) | | | | | |
|-------------------------------|--|--------|--------|--|--|
| Size | 65" | 75" | 86" | | |
| Model | 5653RK | 5753RK | 5863RK | | |
| Accessories | | | | | |
| Cables | AC Power Cable, USB Cable, HDMI Cable | | | | |
| Writing Pen | 2 | | | | |
| Pen Holder | √ (Occupies one USB port) | | | | |
| Remote Control | V | | | | |
| User Manual | √ (Quick Start Guide) | | | | |
| WiFi Module | Optional (SI07B, 2.4G/5G WiFi 6 & BT 5.0) | | | | |
| Wall Mount | Optional (OWMFP01) | | | | |
| Trolley | Optional (ST41B) | | | | |
| Sensor Box | Optional (WL10C), support NFC card for account login & PIR tech & advanced ambient detection. | | | | |
| Apps & Softwar | е | | | | |
| Display Share | $\sqrt{\text{(4-split Mirroring, Live Camera, Laser pointer,}}$ Annotation, Remote View, Moderation, Group Display, Floating Window) | | | | |
| Whiteboard | √ (V, support Google classroom integration (on-site view) & IFP-to-IFP-Web Collaboration | | | | |
| омѕ | (Optional, Support device management) | | | | |
| Annotation | (Support to import image to Whiteboard) | | | | |
| AirShare | (Interactive participation tool) | | | | |
| File Manager | (with multiple cloud storage support) | | | | |
| Google Classroom | (Integrated with Whiteboard) | | | | |
| Auto Pen Detection | (Enable Whiteboard app while picking up pen) | | | | |
| Al Handwriting Recognition | (Support Text, Formula recognition) | | | | |
| Advanced Pen | (Pressure pen, Smart Sketch) | | | | |
| Multi-task Mode | (Dual mode, 4-Windows mode, PIP mode) | | | | |
| Triple Screen Mode | √ (Duplicate/Extension by HDMI/Type C up to extra 2 screens) | | | | |
| Marketplace | (Google PlayStore) | | | | |
| OAM | √ (Optoma Account Management integrates with your account info after login via QR code or NFC card) | | | | |



Crisp visuals with 4K UHD resolution, anti-glare glass, ambient light sensor and cTUVus Eye Comfort Certification for Low Blue Light and Flicker Free



Seamless interactivity with up to 50-point multi-touch capabilities, anti-fingerprint coating and incredible response time



Embedded Android $^{\!\mathsf{TM}}$ system with cutting-edge ARM CPU and Mali GPU







The included pens, ultra-fine touch IR technology and a < 0.6 mm air gap with <1 mm accuracy ensures a natural drawing and annotation feel. Pick up the pen from the holder to instantly trigger Optoma Whiteboard app for a quick and seamless experience that mimics a real whiteboard.

Optional Accessories

Wall Mount with VESA Standard: OWMFP05
Mobile Cart: ST41B
USB WiFi Module: SI07B
NFC Sensor Box: WL10C



