

W400LVe

Bright projection









- Bright WXGA projector 4000 lumens
- Powerful audio with built-in 10W speaker
- ECO+ mode for extended lamp life up to 15,000 hours
- 25,000:1 high contrast



Project bright and vibrant presentations effortlessly any time of day in HD. Designed for meeting rooms and classrooms, the W400LVe boasts amazing colour, long lamp life and energy-saving features for a lower overall cost of ownership.

This projector is easy to connect to with multiple inputs, a built-in speaker and USB Power. Perfect for connecting HDMI dongles such as Google Chromecast or a laptop, PC or Blu-ray player for clear projected images with sound. Portable and lightweight projector can be installed or taken on the move for off-site meetings.

Specifications

 Resolution
 WXGA (1280x800)

 Brightness
 4,000 lumens

 Contrast ratio
 25,000:1

 Native aspect ratio
 16:10

 Aspect ratio - compatible
 4:3,16:9

 Keystone correction - vertical
 +/-40°

 Horizontal scan rate
 15:38 ~ 91.15Khz

 Horizontal scan rate
 15.38 ~ 91.1:

 Vertical scan rate
 50 ~ 85Hz

 Uniformity
 75%

Screen size 0.82m ~ 7.62m (32.24" ~ 300") diagonal

Lamp info
Light source type
Lamp watts
203

 Lamp life hours (up to)
 6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)

 Optical

 Throw ratio
 1.55:1 ~ 1.73:1

 Projection distance
 1m - 12m

 Zoom
 1.1

 Zoom type
 Manual

 Focal length
 21.85 mm~24mm

Native offset 1129

Connectivity Connections

Connections Inputs 1 x HDMI 1.4a 3D support, 1 x VGA, 1 x Composite

video, 1 x Audio 3.5mm

Outputs 1 x VGA, 1 x Audio 3.5mm, 1 x USB-A power 1A

Control 1 x RS232

General

3D compatibility

3D

Noise level (typical) 27dB Noise level (max) 29dB

PC compatibility WUXGA,1080P,UXGA, SXGA+,SXGA

,WXGA+,WXGA,720P,XGA,SVGA,VGAHD, XGA, SVGA, VGA,

Mac

2D compatibilityNTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p,

SECAMI B/D/G/YK1/L, 4.20/4.4WHZ 460/P, 5/60/P, 720p(60/60Hz), 1080i(50/60Hz), 1080p(60/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60

Full 3D

Security Security bar, Kensington Lock, Password protected interface

OSD / display languages 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian,

Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese

Operating conditions 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max

humidity 85%

Speaker count 1
Watts per speaker 10W

In the box

AC power cord
Remote control

Remote control Basic user manual

 Power

 Power supply
 100 ~ 240V, 50 ~ 60Hz

 Power consumption (standby)
 0.5W

 Power consumption (min)
 187W

 Power consumption (max)
 225W

Weight and dimensions

 Dimensions (W x D x H)
 316 x 243.5 x 98

 Gross weight
 3.58 kg

 Net weight
 3 kg





